

## SCR3310/SCR3310v2.0

## **Contact Smart Card Reader**



### **Features**

- · Ergonomic and cost efficient design
- Software and functionality compatible with SCM's SCR33xx readers family
- · In field firmware upgrades\*
- EMV Level 1 certified\*\*
- Compliant with major smart cards and relevant industry standards
- Customization options: Casing color and company logo
- \* for SCR3310 only
- \*\* not applicable for firmware versions without Memory Card support

## **Typical Applications**

The SCR3310 /3310v2 are suitable for a wide range of applications for government applications as well as for enterprise and home useage.

Due to its design, the readers are also ideally suited to be bundlled with smart cards and software to support large scale projects roll outs.

Typical applications areas of the SCR3310 /3310v2 are electronic ID, social security and loyalty programs, e-Couponing, secure network log on, e-Banking as well as online shopping and gaming activities.











#### **Contact Reader**

U.S. Headquarters SCM Microsystems Inc. 41740 Christy Street Fremont, CA 94538 USA E-mail scmsales@scmmicro.com Phone +1 510 360 2300 Fax +1 510 360 0211

European Headquarters SCM Microsystems GmbH Oskar-Messter-Str. 13 85737 Ismaning, Germany E-mail sales@scmmicro.de Phone +49 89 9595 5000 Fax +49 89 9595 5555

SCM Microsystems Japan, Inc. GoogolPlex Millennium Building 6F 4-4-20 Shiba, Minato-ku, Tokyo, Japan 108-0014 E-mail sales@scmmicro.co.jp Phone +81 3 6414 6611 Fax +81 3 6414 6612

SCM Microsystems India Pvt. Ltd. Module No. 0506, 0507 & 0508 D' Block South, 5th Floor Tidel Park, 4 Canal Bank Road Taramani Chennai 600113, India E-mail sales@scmmicro.co.in Phone +91 44 2254 0020 Fax +91 44 2254 0029

www.scmmicro.com



# SCR3310/SCR3310v2.0

#### **Technical Data**

Interfaces		
Host	USB	<ul><li>Full speed USB 2.0 (12 Mbps)</li><li>USB Bus powered device</li><li>CCID compliant</li></ul>
Smart Card	contact	T=0, T=1 protocol support  Memory card support through SCM MCARD API**  Communication speed up to 344 kbps (PPS, FI parameter)  Frequency up to 8 MHz (PPS, DI parameter)  Support ISO 7816 Class A and AB smart card  contacts - ISO 7816 location  100,000 insertions  Friction contact
Human	optical	One green LED
Software	API	PC/SC     CT-API (thru wrapper on top of PC/SC)
Operating Systems		<ul> <li>Windows® Vista, XP, Server 2003, 2000, ME, 98</li> <li>Windows® Vista, XP, Server2003 (AMD64/EMT64)</li> <li>Windows® CE 3.0, 4.1, 4.2, 5.0, 6.0</li> <li>MacOS, Solaris, Linux 32-bit (2.4.x, 2.6.x)/64-bit</li> </ul>
Cable		Cable: 1.5m long with USB type A connector
Dimensions	LxWxH[mm]	• 70 x 70 x 10
Weight	[g]	• 70
Operating Conditions	Temperature[°C] Humidity [%]	• 0 to 50 • 90 (non-condensing)
Approvals	Functional	FCC Class B part 15, cULus, CE, VCCI ANZI (SCR3310) ICES-003 Issue4, ClassB (SCR3310v2.0) USB-IF Microsoft® WHQL 2000, XP, Server2003 EMV 2000 Level 1**
	Environmental	RoHS, WEEE     REACH compliance (SCR3310v2.0)

Technical data are subject to change without notice.

## The SCM Microsystems' Advantage

#### **Trusted Partner**

- ASIC (application specific IC) and smart card reader development experience since 1990
- · Innovative solutions more than 50 patents filed
- Reliable high-quality mass production capability more than 15 Mio. reader solutions deployed to date
- · Active role in standardization committees
- Complex project management expertise

   e.g. U.S. Department of Defense CAC program,
   electronic ID applications (ePassport, health card projects, national ID, driver licence)

#### Support

- · Global presence and support
- Product customization options
- Product branding
- Dedicated Research & Development and customer support team
- Strong global partnership network with leading suppliers along the value chain (smart card manufacturers, application providers, system integrators, device manufacturers)

## **Trusted Products**

- Broadest portfolio of security technology products for governments, corporations, financial institutions, small and medium-sized enterprises and individuals around the globe
- Secure smart chip reader design certified and compliant to EMV, Common Criteria, PC/SC, USB
- High-quality products designed to meet the various requirements in the data security area
- Flexible and future proof solutions SCM's SmartOS™ middleware and its own ASIC technology allow in Field upgrades and secure your investment

<sup>\*\*</sup> EMV 2000 Level 1 certification and memory card support for SCR3310v2.0 on request.