

OMNIKEY® 5321 CL USB Reader



CONTACTLESS USB SMART CARD READER

- **Versatile Applications** – Ideal for end-user environments with different contactless smart card technologies and tags in use
- **Fast Contactless Transmission** – Supports contactless smart cards up to 848 Kbps in fastest ISO 14443 A/B
- **Designed for User Convenience** – Housing design is optimized for advanced contactless applications
- **Readily compliant** – Supports HID® iCLASS® and MIFARE® as well as ISO 14443A/B and ISO 15693

Housed in a robust closed housing with a convenient card retainer, the OMNIKEY® 5321 CL represents the ideal reader for contactless technology applications. Featuring a PC-linked reader that reads/writes to 13.56 MHz contactless smart cards in all three HF standards, the OMNIKEY 5321 CL economically supports end-user environments where a variety of contactless cards and tags are used.

- Supports three ISO standards for contactless cards (ISO 14443 A/B and 15693) and Microsoft WHQL
- Reader supports contactless smart cards with up to 848 Kbps in the fastest ISO 14443 transmission mode
- Standard application interfaces include PC/SC, Synchronous-API (on top of PC/SC), OCF (Open Card Framework) or CT-API

For actual driver downloads please visit hidglobal.com/omnikey

CONTACTLESS TECHNOLOGIES SUPPORTED:

- HID: iCLASS®
- NXP: MIFARE®, DESFire®, SMART-MX and ICODE
- Texas Instruments: TagIT®
- ST Micro: x-ident, SR 176, SR 1X 4K
- Infineon: My-d (in secure mode UID only)
- Atmel: AT088RF020
- KSW MicroTech: KSW TempSens
- iCODE SLI, iCODE SL2 & LRI 64
- Contactless 2048 bit key generation in RSA mode (JCOP / SMART-MX)

SPECIFICATIONS


Model Name	OMNIKEY® 5321
Dimensions	3.78" x 3.07" x .031" (115 x 96.5 x 25.5 mm)
Weight	Approx. 5.64 oz / 160 g
Power Supply	Bus powered
Operating Temperature	32°-131° F (0° - 55° C)
Operating Humidity	10-90% rH
HOST INTERFACE	
Host Interface	USB 2.0 (also compliant with USB 1.1)
Transmission Speed	12 Mbps (USB 2.0 full speed)
CONTACTLESS SMART CARD INTERFACE	
Protocols	T=CL, MIFARE®, iCLASS® / ISO 14443 A with 848 Kbps transmission rate (depending on card) ISO 14443 B with 848 Kbps transmission rate (depending on card) ISO 15693 with 26 Kbps transmission rate (depending on card)
Supported APIs	PC/SC driver (ready for 2.01), Synchronous API (on top of PC/SC)
PC/SC Driver Support	Windows® 2000 / XP (32bit), 2003 Server, 2008 Server Windows® CE 5.0 / 6.0 / CE.NET (depending on hardware), Windows® XP 64bit (AMD64, EM64T, IA64), Windows® Vista (32bit / 64bit), Windows 7 (32bit/64bit), Linux® (in preparation), Mac® OS X 10.5 Leopard
Status Indicator	Dual color LED (green=ready, red=busy)
Reader Board	Also available as PCB
Color	Dark grey
Options	Customer Specific Logo: Available upon request
Composition	ABS
Connector Cable	70.9" (180 cm)
Meantime Between Failure (MTBF)	500,000 hours
Compliance/Certification	Microsoft® WHQL ¹ , USB 2.0 (USB 1.1 compatible), GSA FIPS 201 approved product list (in preparation)
Safety/Environmental	CE, FCC, UL, RoHS, WEEE
Warranty	Two year manufacturer's warranty. (For drivers, see complete lifetime support policy.)

¹ = Windows® Hardware Quality Lab



North America: +1 949 732 2000
Toll Free: 1 800 237 7769
Europe, Middle East, Africa: +49 6123 791 0
Asia Pacific: +852 3160 9800
Latin America: +52 477 779 1492

hidglobal.com

ASSA ABLOY

An ASSA ABLOY Group brand

© 2011 HID Global Corporation. All rights reserved. HID, the HID logo, iCLASS SE, and iCLASS are trademarks or registered trademarks of HID Global in the U.S. and/or other countries. All other trademarks, service marks, and product or service names are trademarks or registered trademarks of their respective owners.
20110511-hid-ok-5321-cl-usb-readers-ds-en