



## OMNIKEY® 5325 USB Prox



### CONTACT AND CONTACTLESS PROX READER

- **Broad Use** - Reads unique number from HID Prox cards, the industry standard for access control
- **Plug-and-Play** - Designed to facilitate easy device installation and automatic configuration
- **Easy Development** - Compliant with a variety of financial institution standards
- **Designed for User Convenience** - Housing design is optimized for advanced contactless applications

The OMNIKEY® 5325 is a high-performance, USB smart card reader for desktop use that can be used with any HID proximity card. Complete with a convenient card retainer and a robust housing, the OMNIKEY® 5325 is compliant with all industry standards. Designed to facilitate ease of use, this dual-interface (contact /contactless) reader works with your existing HID Prox® cards enabling implementation of new logical access applications without re-badging.

Practical and affordable, the OMNIKEY 5325 reader is easy to install and has a transmission speed to the card of up to 420 Kbps, making it an ideal solution for a variety of contact smart card operations, including online banking and / or digital signature applications.


For actual driver downloads please visit [hidglobal.com/omnikey](http://hidglobal.com/omnikey)

### FEATURES:

- Robust housing and long USB cable for increased convenience and reliability
- Supports a variety of PC / SC drivers for contact interface
- Supports ISO 7816 and EMV (Europay®, MasterCard®, Visa®), Microsoft WHQL and HBCI (Home Banking Computer Interface) industry standards for contact cards
- Meets EMV (Europay, MasterCard, Visa), Microsoft WHQL and HBCI (Home Banking Computer Interface) industry standards for contact cards
- RoHS/WEEE compliant
- Broad Use-Reads unique number from HID Prox cards, the industry standard for access control (including all 26-40 bit and Corporate 1000 formats)

### SPECIFICATIONS

<b>Base Model Number</b>	OMNIKEY® 5325
<b>Dimensions</b>	3.78" x 3.07" x .031" (115 x 96.5 x 25.5 mm)
<b>Weight</b>	Approx. 5.01 oz (142 g)
<b>Power Supply</b>	Bus powered
<b>Operating Temperature</b>	32-131 °F (0-55 °C)
<b>Operating Humidity</b>	10-90% rH
<b>HOST INTERFACE</b>	
<b>Host Interface</b>	USB 2.0 CCID <sup>1</sup> (also compliant with USB 1.1)
<b>Transmission Speed</b>	12 Mbps (USB 2.0 full speed)
<b>SMART CARD INTERFACE</b>	
<b>Standards</b>	ISO 7816 & EMV <sup>2</sup> 2000 Level 1
<b>Protocols</b>	T=0, T=1, 2-wire: SLE 4432/42 (S=10); 3-wire: SLE 4418/28 (S=9), I <sup>2</sup> C (S=8)
<b>Card Size</b>	ID-1 (full-size)
<b>Smart Card Interface Speed</b>	420 Kbps (when supported by card)
<b>Smart Card Clock Frequency</b>	Up to 8 MHz
<b>Supported Card Types</b>	5V, 3V and 1.8V Smart Cards, ISO 7816 Class A, B and C
<b>Power to Smart Card</b>	60 mA
<b>Smart Card Detection</b>	Movement detection with auto power-off / Automatic detection of smart card type / Short circuit and thermal protection
<b>8-Pin Handling</b>	C4 / C8 supported
<b>Proximity Card Interface Frequency</b>	HID Prox 125 kHz
<b>Supported APIs</b>	PC / SC driver, CT-API (on top of PC / SC, for contact interface), OCF (on top of PC / SC, for contact interface), Synchronous API (on top of PC / SC, for contact interface)
<b>PC / SC Driver Support</b>	Windows® XP / Vista / Windows 7 / Windows 8, 2003 / 2008 Server, Windows® CE 5.0 / CE.NET / CE 6.0 (depending on hardware), Linux® and Mac® OS X
<b>Status Indicator</b>	Dual-color LED (green = ready, red = busy)
<b>Color</b>	Dark gray
<b>Options</b>	Customer-specific logo, label and colors: available upon request
<b>Reader Board</b>	Available as PCB
<b>Composition</b>	ABS
<b>Connector Cable</b>	70.9" (180 cm)
<b>Durability</b>	100,000 insertions
<b>Meantime Between Failure (MTBF)</b>	500,000 hours
<b>Compliance / Certification</b>	Microsoft® WHQL <sup>3</sup> , EMV <sup>2</sup> 2000 Level 1, ISO 7816, HBCI <sup>4</sup> , USB 2.0 (USB 1.1 compatible), CCID <sup>1</sup> (contact interface only),
<b>Safety / Environmental</b>	CE, FCC, UL, RoHS, WEEE
<b>Warranty</b>	Two-year manufacturer's warranty. (For drivers, see complete lifetime support policy.)



### ASSA ABLOY

An ASSA ABLOY Group brand

©2013 HID Global Corporation/ASSA ABLOY AB. All rights reserved. HID, HID Global, the HID Blue Brick logo, the Chain Design, HID Prox and OMNIKEY are trademarks or registered trademarks of HID Global or its licensor(s)/supplier(s) in the US and other countries and may not be used without permission. All other trademarks, service marks, and product or service names are trademarks or registered trademarks of their respective owners.  
2013-04-15-omnikey-5325-usb-reader-ds-en

North America: +1 949 732 2000

Toll Free: 1 800 237 7769

Europe, Middle East, Africa: +44 1440 714 850

Asia Pacific: +852 3160 9800

Latin America: +52 55 5081 1650